

Acqua *Water*

Rubinetti
Taps

Parinox[®] EPDM







Parinox® EPDM DN6-DN8

Il tubo flessibile PARINOX® EPDM è utilizzato per il collegamento tra la rete idrica e ogni tipo di rubinetto. È stato brevettato negli anni 70 e conta oggi, grazie al suo alto livello qualitativo, milioni di pezzi venduti in Italia e nel mondo. Questo tubo ha ottenuto in Italia e all'estero numerose certificazioni di prodotto. Il tubo PARINOX® è presentato in queste pagine nei due diametri più piccoli, DN6 e DN8. Sono i diametri più adatti per il collegamento tra la rete idrica e i rubinetti miscelatori, compresi quelli con un corpo del rubinetto ridotto in base alle ultime tendenze del design, nonché le cassette W.C. e le macchine del caffè. Garantiscono una portata d'acqua rispettivamente di 18 litri e 32 litri al minuto alla pressione di 3 bar. Caratteristica fondamentale che contraddistingue il tubo PARINOX® dai tubi dei competitors è la garanzia decennale dall'anno di fabbricazione indicato sulla bussola di serraggio.

Parinox®, the traditional EPDM hose, made by Parigi, is used for the connection between water supply net and any kind of taps. Patented in 1975, thanks to its high quality level, it has been sold in million pieces in Italy and all over the world. Being manufactured in compliance with international rules in this field, this hose has obtained numerous product approvals in Italy and abroad. The smallest Parinox® hoses DN6 and DN8 are mostly suitable for the connection between water supply net and mixer taps, especially those with a reduced body tap, in accordance with the last tendency of the designers, and W.C. tanks and coffee machines. The 10 years guarantee, calculated from the production year marked on the sleeves, is a distinguishing mark of Parinox® hose in comparison with all similar products made by the competitors.

Tubo di gomma <i>Rubber hose</i>	Treccia <i>Braiding</i>	Raccordi <i>Fittings</i>	Bussole <i>Sleeves</i>	Raggio di curvatura <i>Bending radius</i>	Pressione d'esercizio <i>Working pressure</i>	Temperatura d'esercizio* <i>Working Temperature*</i>	Foro sui raccordi <i>Passage hole</i>	Portata d'acqua <i>Water supply</i>	Confezione <i>Packaging</i>
EPDM  mm	INOX AISI 304  Ø mm	 CW 614N	 INOX	 R = mm	 bar	 °C	 mm	 lt/min - 3 bar	
DN6 - 6.2 DN8 - 8	10 12		Ø mm 12 Ø mm 14	25 30	10 10	-5 + 90 -5 + 90	4.7 6.2	18 32	125 100

Raccordi - Fittings

	F	1/8c 1/4NPSM 3/8NPSM 15x1 1/2NPSM	1/4 3/8 9/16 15/16 3/4	1/4c 3/8c 9/16c 1/2		MOM	8/1	10x1	11x1
	FGL	3/8 1/2NPSM	9/16 15/16	1/2		MOL	8/1	10x1	11x1,25
	FG	3/8 Brevetto Europeo Europea patent	1/2			MDB	10 14	12 15	
	M	1/4 1/2	1/4NPT 3/8			CF	1/8c 3/8 1/2	1/4c 3/8c 3/4	
	M	con anello PTFE with PTFE ring	3/8 1/2			CFGL	3/8		1/2
	MG	3/8	1/2			TL	6 10	8 12	
	MOK	8/1 11x1,25	10x1 11x24	11x1 12x1		Mvalv.	1/2		

I raccordi possono essere fabbricati anche in ottone CW 602N(ADZ). Parigi produce anche tubi flessibili equipaggiati con raccordi fabbricati su disegno del cliente.

Our fittings can be manufactured also in CW 602N Brass (DR-Brass). Parigi can also manufacture hoses equipped with fittings made according to customers drawings.



Parinox® EPDM DN10-DN13-DN16

Grande portata d'acqua per i tubi Parinox® disponibili dal DN10 al DN16. Anch'essi dotati di treccia esterna in acciaio inossidabile, raccordi di ottone nichelato, bussole in acciaio inossidabile, garantiscono una portata d'acqua che, a seconda del diametro, può variare da 48 a 160 litri al minuto a una pressione di 3 bar.



Sono utilizzati prevalentemente per il collegamento tra la rete idrica e i rubinetti singoli, gli scaldabagni, le pareti doccia attrezzate, e le vasche idromassaggio, i rubinetti posti sulle cucine industriali. Sono anch'essi garantiti 10 anni dalla data di fabbricazione indicata sulle bussole di serraggio.

Big water supply for the Parinox® hoses from DN10 to DN16. They are covered by a stainless steel braiding and equipped with nickel plated brass fittings and stainless steel sleeves. Their water supply can go from 48 to 160 litres per minute at 3 bar working pressure.

They are mostly used for the connection between water supply net and single hole taps, especially those installed on industrial kitchens, water heaters, shower panels and whirlpool systems. They have a 10 years guarantee, calculated from the production year marked on the sleeves.

Tubo di gomma <i>Rubber hose</i>	Treccia <i>Braiding</i>	Raccordi <i>Fittings</i>	Bussole <i>Sleeves</i>	Raggio di curvatura <i>Bending radius</i>	Pressione d'esercizio <i>Working pressure</i>	Temperatura d'esercizio* <i>Working Temperature*</i>	Foro sui raccordi <i>Passage hole</i>	Portata d'acqua <i>Water supply</i>	Confezione <i>Packaging</i>
EPDM  mm	INOX AISI 304  Ø mm	 CW 614N	 INOX	 R = mm	 bar	 °C	 mm	 lt/min - 3 bar	
DN10 - 9,5 DN13 - 13 DN16 - 16	14 18,5 23		Ø mm 16,5 Ø mm 21 Ø mm 25	35 40 60	10 10 10	-5 + 90 -5 + 90 -5 + 90	7,5 10 13	48 76 160	50 25 10

Raccordi - Fittings

	F	3/8 1/2 3/4	3/8c 1/2c 3/4c	15x1 15/16		CFG	1/2 3/4	
	FGI	3/8	1/2	3/4		MDB	10 15	12 22 14
	FG	1/2	Brevetto Europeo Europea patent			TL	10	12 15
	M	1/4 1/2c	3/8 1/2NPT	1/2 3/4		FALOR	1/2	
	MG	3/8	1/2			Mvalv.	1/2	
	MOK	12x1				M	con anello PTFE with PTFE ring	3/8 1/2
	CF	3/8 1/2c	3/8c 3/4	1/2		CFG	1/2	
						CMG	1/2 3/4	

I raccordi possono essere fabbricati anche in ottone CW 602N(ADZ). Parigi produce anche tubi flessibili equipaggiati con raccordi fabbricati su disegno del cliente.

Our fittings can be manufactured also in CW 602N Brass (DR-Brass). Parigi can also manufacture hoses equipped with fittings made according to customers drawings.



High Quality Flexible Hoses

20052 Monza (MI) Italy - Via Velleia, 19 - Tel. +39.039.204981 - Fax +39.039.832016
Internet: www.parigispa.com - E-mail: parigi@parigispa.com